

## SANFLEX 2m

| Dimension            | Unit | Unit/Box |
|----------------------|------|----------|
| <b>Debljina 6mm</b>  |      |          |
| 012-06/2m Sanflex    | M    | 560      |
| 015-06/2m Sanflex    | M    | 440      |
| 018-06/2m Sanflex    | M    | 400      |
| 020-06/2m Sanflex    | M    | 340      |
| 022-06/2m Sanflex    | M    | 320      |
| 025-06/2m Sanflex    | M    | 290      |
| 028-06/2m Sanflex    | M    | 250      |
| 032-06/2m Sanflex    | M    | 210      |
| 035-06/2m Sanflex    | M    | 180      |
| 042-06/2m Sanflex    | M    | 150      |
| <b>Debljina 9mm</b>  |      |          |
| 012-09/2m Sanflex    | M    | 456      |
| 015-09/2m Sanflex    | M    | 380      |
| 018-09/2m Sanflex    | M    | 330      |
| 020-09/2m Sanflex    | M    | 250      |
| 022-09/2m Sanflex    | M    | 250      |
| 025-09/2m Sanflex    | M    | 190      |
| 028-09/2m Sanflex    | M    | 190      |
| 032-09/2m Sanflex    | M    | 150      |
| 035-09/2m Sanflex    | M    | 150      |
| 042-09/2m Sanflex    | M    | 110      |
| 048-09/2m Sanflex    | M    | 90       |
| 054-09/2m Sanflex    | M    | 70       |
| 060-09/2m Sanflex    | M    | 66       |
| 063-09/2m Sanflex    | M    | 66       |
| 076-09/2m Sanflex    | M    | 66       |
| <b>Debljina 13mm</b> |      |          |
| 015-13/2m Sanflex    | M    | 256      |
| 018-13/2m Sanflex    | M    | 220      |
| 022-13/2m Sanflex    | M    | 180      |
| 028-13/2m Sanflex    | M    | 140      |
| 035-13/2m Sanflex    | M    | 120      |
| 042-13/2m Sanflex    | M    | 90       |
| 048-13/2m Sanflex    | M    | 70       |
| 060-13/2m Sanflex    | M    | 48       |
| 063-13/2m Sanflex    | M    | 48       |
| 76-13/2m Sanflex     | M    | 40       |

## SANFLEX STABIL 2m

| Dimension                | Unit | Unit/Box |
|--------------------------|------|----------|
| <b>Debljina 6mm</b>      |      |          |
| 015-06/2m Sanflex Stabil | M    | 440      |
| 018-06/2m Sanflex Stabil | M    | 400      |
| 022-06/2m Sanflex Stabil | M    | 320      |
| 028-06/2m Sanflex Stabil | M    | 250      |
| 035-06/2m Sanflex Stabil | M    | 180      |

## SANFLEX STABIL 10m

| Dimension                    | Unit | Unit/Box |
|------------------------------|------|----------|
| <b>Debljina 6mm</b>          |      |          |
| 015-06/10m B1 Sanflex Stabil | M    | 300      |
| 018-06/10m B1 Sanflex Stabil | M    | 270      |
| 022-06/10m B1 Sanflex Stabil | M    | 250      |
| 028-06/10m B1 Sanflex Stabil | M    | 220      |
| 035-06/10m B1 Sanflex Stabil | M    | 180      |



### DISTRIBUTER:

Valmaks tim doo  
Vodovodska 164e  
11000 Beograd, Srbija  
Tel.: +381 11 2570 301  
E-Mail: office@valmaks.rs

nmc Polska Sp. z o.o.  
Ul. Pyskowicka 15,  
41-807 Zabrze – Polska  
Tel.: +48 32 373 24 40  
E-Mail: biuro@nmc.pl



Insulation technologies

## SANFLEX



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX izolacija takodje obezbedjuje dobru zvučnu absorpciju.

### Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Termička provodljivost (W/m2K) | $\lambda=0,038$ at 16°C |
|                                | $\lambda=0,040$ at 40°C |
|                                | $\lambda=0,049$ at 75°C |
| Opseg temperature              | 0°C - 100°C             |
| Protivpožarna klasa            | Euroclass E             |
| Nivo buke (smanjenje)          | 23dB(A)                 |
| Dužina                         | 2m komad                |

## SANFLEX STABIL 2m



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX Stabil 2m izolacija takodje obezbedjuje dobru zvučnu absorpciju i zaštitu od oštećenja. Izolacija je dostupna u 2 boje: crvena i plava

### Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Termička provodljivost (W/m2K) | $\lambda=0,038$ at 16°C |
|                                | $\lambda=0,040$ at 40°C |
|                                | $\lambda=0,049$ at 75°C |
| Opseg temperature              | 0°C - 100°C             |
| Protivpožarna klasa            | Euroclass E             |
| Nivo buke (smanjenje)          | 23dB(A)                 |
| Dužina                         | 2m komad                |

## SANFLEX STABIL 10m



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX Stabil 10m izolacija takodje obezbedjuje dobru zvučnu absorpciju i zaštitu od oštećenja. Pakovanja od 10m su veoma praktična i omogućavaju uštedu u prostoru. Izolacija je dostupna u 2 boje: crvena i plava

### Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Termička provodljivost (W/m2K) | $\lambda=0,038$ at 16°C |
|                                | $\lambda=0,040$ at 40°C |
|                                | $\lambda=0,049$ at 75°C |
| Opseg temperature              | 0°C - 100°C             |
| Protivpožarna klasa            | Euroclass E             |
| Nivo buke (smanjenje)          | 23dB(A)                 |
| Dužina                         | 10m komad               |